



Открытое акционерное общество
 “Белорусский металлургический завод —
 управляющая компания холдинга
 “Белорусская металлургическая компания”

Ул. Промышленная, 37, 247210, г. Жлобин, Гомельская обл.
 Тел. +375 (2334) 5 45 20, 5 46 31; факс +375 (2334) 3 10 70, 3 16 35,
 email: ofwork@bmz.gomel.by

Р.с. 3012003880014 в филиале 312 ОАО СБ “Беларусбанк” г. Жлобина,
 МФО 151501673, УНП 400074854

Open Joint-Stock Company
 “Byelorussian Steel Works — management company of
 “Byelorussian Metallurgical Company” holding”

37 Promyshlennaya St, 247210, Zhlobin, Gomel region.
 Tel. +375 2334 2 50 99, 5 55 20; fax +375 2334 3 10 70, 3 16 35,
 email: ofwork@bmz.gomel.by

Acc. No. 301200380014 with JSCB “BELARUSBANK”, branch 312, Zhlobin,
 MFO 151501673, TRN 400074854

29.04.2016 № 4/358a
 На № _____ от _____

Declaration of performance

(European construction regulations №305/2011, Annex III)
№ 1.0149/S275J0H- CPR-1011

1. Unique identification code of product type: **S275J0H – EN 10210-1, -2**
 2. Product name: **Hot-rolled seamless hollow sections steel from unalloyed steel for metal structures**
 3. Manufacturer: **Open Joint Stock Company
 «Byelorussian steel works — management company of «Byelorussian metallurgical company» holding»
 37, Promyshlennaya str., 247210, Zhlobin, Republic of Belarus
 Tel/fax +375 2334 54129
 e-mail: qualdir@bmz.gomel.by www.belsteel.com**
 4. Name and address of an authorized representative of the manufacturer acting under mandate: **Not applicable**
 5. System for assessment and verification of performance characteristics: **System 2+**
 - 6a. Harmonized specification: **EN 10210-1:2006**
 - Name and number of notified institution that issued a certificate: **Institution for certification of construction products and metal constructions registered under №0045 TÜV NORD System GmbH &Co.KG (Hamburg, Germany)**
 - 6b. European assessment document: **Not applicable**
- № 1.0149/S275J0H-CPR-1011



7. Declared performance:

Essential characteristics	Performance						Harmonized technical specification
Size	Nominal outer diameter: from 21,3 to 168,3mm Wall thickness from 2,3 to 25mm						EN10210-1:2006
Yield strength	Wall thickness, mm		R_{eH} , MPA, min				
	(Table A.3)						
	≤ 16		275				
Tensile strength	Wall thickness, mm		R_m , MPA				
	(Table A.3)						
	≤ 3		430-580				
Percent elongation	Wall thickness, mm		A, %, min				
	(Table A.3)						
	≤ 25		23				
Impact strength	Test temperature, °C		KV^e , J, min				
	(Table A.3)						
Carbon equivalent	0		27				
	Wall thickness, mm		C_{equiv} , %, max				
	(Table A.2)						
Chemical composition	≤ 16		0,41				
	$> 16 \leq 25$		0,43				
	Max mass fractions, % (Table A.1)						
	C	Si	Mn	P	S	N	
	0,20	-	1,50	0,035	0,035	0,009	

8. Appropriate technical documents and/or specific technical documents Not applicable

The performance of the product identified in point 1 is in conformity with the performance characteristics declared in point 7.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer

Deputy General Director for Technology and Quality Management
Name and function

Zhlobin

Place and date of issue



E.A. Peretyagina

Signature, stamp