



Министерство промышленности Республики Беларусь  
Производственное объединение  
"Белорусский металлургический завод"  
Открытое акционерное общество  
"Белорусский металлургический завод"  
Ул. Промышленная, 37, 247210, г. Жлобин, Гомельская обл.  
Тел. +375 2334 2 50 99, 5 55 20, факс +375 2334 2 42 61, 3 16 35,  
email: ofwork@bmz.gomel.by

Р.с. 3012003880014 в филиале 312 ОАО СБ "Беларусбанк" г. Жлобина,  
МФО 151501673, УНП 400074854

Ministry of Industry of the Republic of Belarus  
Production association  
"Byelorussian Steel Works"  
Open Joint-Stock Company  
"Byelorussian Steel Works"  
37 Promyshlennaya St, 247210, Zhlobin, Gomel region.  
Tel. +375 2334 2 50 99, 5 55 20, fax +375 2334 2 42 61, 3 16 35,  
email: ofwork@bmz.gomel.by

Acc. No. 3012003880014 with JSCB "BELARUSBANK", branch 312, Zhlobin,  
MFO 151501673, TRN 400074854

25.04.2016 № 4/334a  
На № \_\_\_\_\_ от \_\_\_\_\_

**Declaration of performance**  
**(European construction regulations №305/2011, Annex III)**

**№ 1.0577 / S355J2-CPR-1011**

- |  |   |
|--|---|
| 1. Unique identification code of product type  | S355J2 - EN 10025-2:2005-04   |
| 2. Product name  | Hot-rolled bars of construction steel for metalware   |
| 3. Manufacturer  | Open Joint Stock Company<br>«Byelorussian steel works — management company of «Byelorussian metallurgical company» holding»<br>37, Promyshlennaya str., 247210, Zhlobin, Republic of Belarus<br>Tel/fax +375 2334 54129<br><b>e-mail: <a href="mailto:qualdir@bmz.gomel.by">qualdir@bmz.gomel.by</a> <a href="http://www.belsteel.com">www.belsteel.com</a></b> |
| 4. Name and address of an authorized representative of the manufacturer acting under mandate | Not applicable  |
| 5. System for assessment and verification of performance characteristics                     | System 2+   |
| 6a. Harmonized specification   | EN 10025-2:2005-04  |
| - Name and number of notified institution that issued a certificate                          | Institution for certification of construction products and metal constructions registered under №0045 TÜV NORD System GmbH & Co.KG (Hamburg, Germany)   |
| 6b. European assessment document   | Not applicable  |



7. Declared performance

Essential characteristics	Performance characteristics		Harmonized technical specifications						
Diameter	from 5,5 to 160mm		EN 10060:2003 (table 1)						
Yield strength	Diameter, mm	$R_{eH}$ , MPa, min	EN 10025-2:2005-04 (table 7)						
	5,5 - 16	355							
	17 - 40	345							
	41 - 63	335							
	64 - 80	325							
	85 - 100	315							
	105 - 150	295							
	160	285							
Tensile strength	Diameter, mm	$R_m$ , MPa							
	5,5 - 100	470-630							
	105 - 160	450-600							
Specific elongation	Diameter, mm	$L_{0,2}$ , %, min							
	5,5 - 40	22							
	41 - 63	21							
	64 - 100	20							
	105 - 150	18							
	160	17							
Impact strength	Diameter, mm	$KV^c$ , J, at -20 °C, min	EN 10025-2:2005-04 (table 9)						
	5,5 - 160	27							
Carbon equivalent	Diameter, mm	C equiv., %, max	EN 10025-2:2005-04 (table 6)						
	5,5 - 30	0,45							
	31 - 150	0,47							
	160	0,49							
Chemical composition	Max. mass fraction, %							EN 10025-2:2005-04 (table 2)	
	C		Si	Mn	P	S*	N		Cu
	≤16	>40							
	≤40	0,22	0,55	1,60	0,025	0,025	-		0,55
Note: * It is allowed to exceed max fraction of sulfur up to 0,040%, according to subparagraph e) of table 2									

8. Appropriate technical documents and/or specific technical documents Not applicable

The performance of the product identified in point 1 is in conformity with the performance characteristics declared in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Deputy General Director for Technology and Quality

Name and function



signature

*25/04/16*

A. Peretyagina

Zhlobin

Place and date of issue